



Kanalstål - UNP S355J2

Tekniske lev. betingelser: NS-EN 10025-2

Toleranse etter NS-EN 10 279

Dokumenter etter NS-EN 10204-3.1 CE merket

Leveringstilstand M eller AR

		kg pr. lengde		mål i mm			
UNP	pr. m	6	12	Høyde	Bredde	Steg	Flens
*65	7,3	53		65	42	5,5	7,5
80	8,9	66	131,0	80	45	6,0	8,0
100	11,0	83	166,0	100	50	6,0	8,5
120	13,8		198,0	120	55	7,0	9,0
140	16,5		232,0	140	60	7,0	10,0
160	19,4		Skaffevare	160	65	7,5	10,5
180	22,7		313,2	180	70	8,0	11,0
200	26,1		skaffevare	200	75	8,5	11,5
220	30,3		Skaffevare	220	80	9,0	12,5
240	34,3		Skaffevare	240	85	9,5	13,0
260	39,1		Skaffevare	260	90	10,0	14,0
280	43,0		Skaffevare	280	95	10,0	15,0
300	47,6		571,0	300	100	10,0	16,0
320	61,3		736,0	320	100	14,0	17,5

De lengdene som har ferdig utfylt vekt pr. lengde, lagerføres normalt.

*UNP65 i S235JR kvalitet.